



## Product Data

### **Castrol Brayco 922**

Calibrating Fluid  
Aircraft Fuel System Components

#### **Description**

Castrol Brayco™ 922 is a special run, stoddard solvent calibrating fluid.

#### **Temperature Range**

Brayco 922 is designed to operate over the temperature range of 10°C to 30°C (50°F to 86°F)

#### **Application**

Brayco 922 is designed for use in the calibration of fuel system components for aircraft reciprocating engines and aircraft gas turbines. It is compatible with Nitrile, PVA and Viton, but not recommended for use with butyl rubber, natural rubber, neoprene or EPDM.

#### **Specification**

Brayco 922 meets the requirements of MIL-PRF-7024E, Type II.

## Typical Characteristics

TEST (ASTM)	DESCRIPTION	SPECIFICATION REQUIREMENT	RESULT
D 286	Gravity, API @ 60°F (16°C)	51.0 - 53.5	53.0
D 1298	Specific Gravity @ 60/60°F (16/16°C)	0.765 - 0.775	0.77
Table 8	Pounds per Gallon @ 60°F (16°C)	6.368 - 6.455	6.38
D 445	Viscosity @ 77°F (25°C), cSt	1.12 - 1.22	1.19
D 381	Gum, Existent, mg/100 ml	5.0 Maximum	1
D 86	Distillation Initial Boiling Point, °F (°C) Final Boiling Point, °F (°C) Recovery, %	300 (150) Minimum 410 (212) Maximum 98.5 Minimum	310 (156) 345 (175) 99
D 56	Flash Point, TCC, °F (°C)	100 (38) Minimum	104 (40)
D 235	Mercaptan Sulfur, % (or Doctor Test)	0.001 Maximum	Pass
D 130	Copper Corrosion 3 hrs @ 212°F (100°C)	1 Maximum	1 1b
D 1319	Aromatics, % Volume	20 Maximum	0.7
D 1319	Olefins, % Volume	5.0 Maximum	1.0
D 2276	Particulate Matter, mg/liter	2.0 Maximum	0.55
D 3242	Total Acid Number, mgKOH/gm	0.015 Maximum	0.005

Subject to usual manufacturing tolerances.

Castrol Brayco 922  
8/8/2008, version 6.0  
Castrol, Brayco and the Castrol logo are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563  
Tel: (877) 641 1600 Fax: (877) 648 9801  
[www.castrol.com/industrial](http://www.castrol.com/industrial)