



Braycote 610

Grease, Automotive and Artillery

Description

Castrol Braycote™ 610 is an advanced lithium-complex thickened, amber-colored multi-purpose NLGI Grade 2 grease. This product is composed primarily of synthetic hydrocarbon base stocks, gelling agents, anti-oxidants and corrosion inhibiting additives.

Application

Braycote 610 is intended for use as a long-life, general-purpose lubricant and to provide surface corrosion protection of all ground vehicles and equipment. It is also an excellent lubricant for automotive and industrial applications where a wide temperature range or where infrequent re-greasing is preferred. This grease may be used in other applications where a NLGI Grade 2 grease with good oxidation and salt water corrosion resistance is desirable.

Typical Physical Characteristics

	Unit	Test Method	Typical Value
Worked Penetration (25°C, 60 str)	mm ⁻¹	ASTM D 217	281
Worked Stability – Percent Change (25°C, 100,000 double strokes)	%	Spec. 4.7.5	33
Dropping Point	°C / °F	ASTM D 2265	264 / 507
Evaporation Loss (22 hrs, 99°C)	%	ASTM D 972	2.5
Oil Separation During Storage (24 hrs, 25°C, 0.25 psi air)	%	ASTM D 1742	1.6
Copper Strip Corrosion (24 hrs, 100°C)	-	ASTM D 4048	1a
Rust Prevention Rating (Salt Water, 48 hrs, 52°C)	-	ASTM D 1743 Mod	Pass 1, 1, 1
Oxidation Stability, Pressure Drop 100 hrs 400 hrs	kPa	ASTM D 942	4 17
Four Ball Wear, Scar Diameter (40 kgf, 1 hr, 75°C, 1200 RPM)	mm	ASTM D 2266	0.43
Four Ball EP Weld Point Load Wear Index	kg -	ASTM D 2596	250 44
Timken OK Load	lb	ASTM D 2509	30

	Unit	Test Method	Typical Value
Low Temperature Torque (54°C)			
Initial	N-m	ASTM D 4693	3.68
Running, 5 minutes			1.69
Life Test, Automotive Wheel Bearing (1000 rpm, 160°C)	hours	ASTM D 3527	160
Roll Stability Test – Penetration change (2hrs, 165 RPM)	%	ASTM D 1831	18
Water Stability Test – Penetration Change (25°C, 10% water, 100,000 strokes)	%	Spec. 4.7.3	19

Subject to usual manufacturing tolerances

Additional Information

Temperature Range Braycote 610 is designed to operate over the temperature range of -54°C to 121°C (-65°F to 250°F). Specification Braycote 610 meets the requirements of and is qualified to MIL-PRF-10924H. NATO Code Number: G-403. Military Symbol: GAA.

Braycote 610
30 Jun 2011
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial