



## 1. Product and company identification

**Product name** Brayco 922

**MSDS #** 452701

**Historic MSDS #:** ~~2~~7034

**Code** ~~4~~52701-US03

**Product use** Calibration fluid.  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

**Manufacturer** Castrol Industrial North America, Inc.  
150 W. Warrenville Road  
Naperville, IL 60563

**Supplier** Wakefield Canada, Limited  
3620 Lakeshore Blvd West  
Toronto, Ontario, Canada  
M8W 1P2

Castrol Industrial North America, Inc.  
150 W. Warrenville Road  
Naperville, IL 60563  
Product Information: +1-877-641-1600

**EMERGENCY SPILL INFORMATION:** 1 (613) 996-6666 CANUTEC (Canada)  
1 (703) 527-3887 CHEMTREC (USA)

## 2. Hazards identification

**Physical state** Liquid.

**Color** Colorless.

**Emergency overview** WARNING !

COMBUSTIBLE LIQUID AND VAPOR.  
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION.  
ASPIRATION HAZARD.  
HARMFUL OR FATAL IF SWALLOWED.  
CAN ENTER LUNGS AND CAUSE DAMAGE.

Combustible liquid. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. Aspiration hazard if swallowed. Can enter lungs and cause damage. Keep away from heat, sparks and flame. Do not breathe vapor or mist. Do not ingest. If ingested, do not induce vomiting. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

**Routes of entry** ermal contact. Eye contact. Inhalation.

**Potential health effects**

**Eyes** Causes eye irritation.

**Skin** Causes skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

**Inhalation** Causes respiratory tract irritation. May cause nausea, dizziness, headaches and drowsiness if high concentrations of vapor are inhaled.

**Ingestion** Aspiration hazard if swallowed. Can enter lungs and cause damage. Ingestion may cause gastrointestinal irritation and diarrhea.

See toxicological information (Section 11)

<b>Product name</b> Brayco 922	<b>Product code</b> <del>4</del> 52701-US03	<b>Page:</b> 1/6
<b>Version</b> 5	<b>Date of issue</b> 03/26/2014.	<b>Format</b> Canada
	(Canada)	<b>Language</b> ENGLISH (ENGLISH)

### 3. Composition/information on ingredients

Ingredient name	CAS #	%
Petroleum naphtha Distillates (Petroleum) hydrotreated light	64742-88-7	45 - 50
	64742-47-8	45 - 50

### 4. First aid measures

<b>Eye contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
<b>Skin contact</b>	Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Clean shoes thoroughly before reuse. Wash contaminated clothing before reuse. Get medical attention.
<b>Inhalation</b>	If inhaled, remove to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Get medical attention.
<b>Ingestion</b>	Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

### 5. Fire-fighting measures

<b>Flammability of the product</b>	Combustible liquid and vapor.
<b>Flash point</b>	Closed cup: 40°C (104°F) [Tagliabue.]
<b>Fire/explosion hazards</b>	In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
<b>Extinguishing media</b>	
<b>Suitable</b>	Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
<b>Not suitable</b>	Do not use water jet.
<b>Fire-fighting procedures</b>	☑ Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
<b>Hazardous combustion products</b>	Combustion products may include the following: carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide)
<b>Protective clothing (fire)</b>	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

<b>Personal precautions</b>	No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
<b>Environmental precautions</b>	☑ Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
<b>Methods for cleaning up</b>	

## Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Small spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7. Handling and storage

### Handling

Put on appropriate personal protective equipment (see Section 8). Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

### Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### Ingredient name

#### Occupational exposure limits

Petroleum naphtha

#### CA Quebec Provincial (Canada).

TWAEV: 400 ppm 8 hours. Issued/Revised: 1/2000

TWAEV: 1590 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/2000

Distillates (Petroleum) hydrotreated light

#### CA British Columbia Provincial (Canada). Absorbed through skin.

TWA: 200 mg/m<sup>3</sup>, (as total hydrocarbon vapour) 8 hours. Issued/Revised: 8/2004

#### CA Alberta Provincial (Canada). Absorbed through skin.

8 hrs OEL: 200 mg/m<sup>3</sup>, (as total hydrocarbon vapour) 8 hours. Issued/Revised: 7/2009

#### CA Ontario Provincial (Canada). Absorbed through skin.

TWA: 200 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/2003

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

### Control Measures

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

### Personal protection

**Eyes** Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

**Product name** Brayco 922

**Product code** 52701-US03

**Page:** 3/6

**Version** 5 **Date of issue** 03/26/2014.

**Format** Canada  
(Canada)

**Language** ENGLISH  
(ENGLISH)

**Skin and body**

Do not get on skin or clothing. Wear suitable protective clothing.

**Respiratory**

Use adequate ventilation. Avoid breathing vapor or mist.

**Hands**

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

---

## 9. Physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Color</b>	Colorless.
<b>Odor</b>	Mild. Hydrocarbon.
<b>Odor threshold</b>	Not available.
<b>Flash point</b>	Closed cup: 40°C (104°F) [Tagliabue.]
<b>Specific gravity</b>	0.771 [at 20°C]
<b>pH</b>	Not available.
<b>Viscosity</b>	Kinematic: <7 mm <sup>2</sup> /s (<7 cSt) at 40°C
<b>Boiling point / Range</b>	>154°C (>309.2°F)
<b>Melting point / Range</b>	Not available.
<b>Vapor pressure</b>	0.173 kPa (1.3 mm Hg) at 20°C
<b>Vapor density</b>	4.7 [Air = 1]
<b>Evaporation rate</b>	Not available.
<b>Solubility</b>	insoluble in water.
<b>LogK<sub>ow</sub></b>	Not available.

---

## 10. Stability and reactivity

<b>Stability and reactivity</b>	The product is stable.
<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	Avoid all possible sources of ignition (spark or flame).
<b>Incompatibility with various substances</b>	Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
<b>Hazardous polymerization</b>	Under normal conditions of storage and use, hazardous polymerization will not occur.

---

## 11. Toxicological information

<b>Other Toxicity Data</b>	Vapors may cause headaches, dizziness and central nervous system depression.  Contains material that may cause target organ damage, based on animal data. Target Organs: Liver and Kidneys.
<b>Potential chronic health effects</b>	
<b>Carcinogenicity</b>	No known significant effects or critical hazards.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Teratogenicity</b>	No known significant effects or critical hazards.
<b>Fertility effects</b>	No known significant effects or critical hazards.

**Reproductive effects**

No known significant effects or critical hazards.

**Medical conditions aggravated by over-exposure**

None known.

**12. Ecological information****Ecotoxicity**

No testing has been performed by the manufacturer.

**13. Disposal considerations****Waste information**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal**

**14. Transport information****International transport regulations**

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
<b>DOT Classification</b>	UN1268	PETROLEUM DISTILLATES, N.O.S. (Petroleum naphtha)	3	III	The product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials.
<b>TDG Classification</b>	UN1268	PETROLEUM DISTILLATES, N.O.S. (Petroleum naphtha)	3	III	-
<b>IMDG Classification</b>	UN1268	PETROLEUM DISTILLATES, N.O.S. (Petroleum naphtha). Marine pollutant	3	III	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.  <b>Emergency schedules (EmS)</b> F-E, S-E
<b>IATA/ICAO Classification</b>	UN1268	PETROLEUM DISTILLATES, N.O.S. (Petroleum naphtha)	3	III	The environmentally hazardous substance mark may appear if required by other transportation regulations.

## 15. Regulatory information

**WHMIS (Canada)** Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).  
Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### Other regulations

<b>Canada inventory</b>	All components are listed or exempted.
<b>United States inventory (TSCA 8b)</b>	All components are listed or exempted.
<b>REACH Status</b>	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.
<b>Australia inventory (AICS)</b>	All components are listed or exempted.
<b>China inventory (IECSC)</b>	All components are listed or exempted.
<b>Japan inventory (ENCS)</b>	All components are listed or exempted.
<b>Korea inventory (KECI)</b>	All components are listed or exempted.
<b>Philippines inventory (PICCS)</b>	All components are listed or exempted.

## 16. Other information

<b>Label requirements</b>	WARNING !  COMBUSTIBLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. ASPIRATION HAZARD. HARMFUL OR FATAL IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE.
---------------------------	---

### History

<b>Date of issue</b>	03/26/2014.
<b>Date of previous issue</b>	03/23/2011.
<b>Prepared by</b>	Product Stewardship

Indicates information that has changed from previously issued version.

### Notice to reader

*All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.*

*The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.*

*It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.*

<b>Product name</b> Brayco 922	<b>Product code</b> 52701-US03	<b>Page:</b> 6/6
<b>Version</b> 5	<b>Date of issue</b> 03/26/2014.	<b>Format</b> Canada
	<b>(Canada)</b>	<b>Language</b> ENGLISH <b>(ENGLISH)</b>